



Sea Dragon 4500  
Pro Photo/ Video Light  
(Item SL675)

**START**

**What's in the box:**



Sea Dragon 4500 light head with YS adapter attached

Flex-Connect YS adapter



1" ball joint adapter with w/ hex key



50W Li-ion battery with protective cover, charging tray and AC power adapter



Int'l plug adapters for EU, UK and AU



Spare O-rings w/ lube and removal tool



Carry Case

1

**Charge the battery.**

Status light on AC power adapter turns from red to green when battery is fully charged. Note: Battery is pre-installed in the light. Remove yellow contact cover, which prevents accidental power on during transportation.



2


**Check if O-rings are lubed.**

O-ring should appear shiny. If not, apply small amount of silicon lube to outside surface of O-rings. Wipe off excess lube.



3

Insert battery in light and screw on waterproof battery cap until fully seated.




4

Connect light head to arm or grip (Sold separately). Use Flex-Connect YS adapter if connecting light to Flex-Connect system of arms, grips and trays. Light may also be mounted directly to YS arms and grips. Replace YS adapter with included ball joint adapter if mounting to ball joint arms and grips.



5

Push and hold power button for 1 second to power light on and off.



6

Push and release the power button to cycle through 5 different brightness modes: 100% 75% 50% 25% Auto [repeat].

7

Battery status indicator will be green when battery is 30% to 100% charged, yellow when battery is 15% to 29% charged and red when battery is near empty. There is a 10-minute 70-lumen safety reserve before light powers off when battery is empty and - status indicator will blink red.

8

To activate emergency signal mode, push and hold power button for 4 seconds from power off state. Push and release power button to select between 1 sec blink interval and SOS Morse code.

9

The Auto Flash Detect (AFD) feature is already activated. The light will power off for 1 sec. when nearby flash is fired. To deactivate AFD, push and hold power button for 5 seconds from power off state. Push and release power button to select between AFD off (1 blink per sec.) and AFD on (2 blinks).

